


Unmanaged Switch PROmesh U8

PROmesh U8



Art. No.: 114110122

HIGHLIGHTS



8 RJ45 Ports



Industrial Applications

- PROFINET



Country approvals

- CE | UKCA



Performance

- Memory: 1 MB
- Backplane capacity: 1,6 Gbps
- Throughput: 1,19 Mpps



Sustainability

- Lead-free
- Lowpower consumption

Unmanaged Switch PROmesh U8

Technical details

Network interfaces	
RJ45 Ports	
■ Interfaces	8
■ Transmission rates	10 Mbps 100 Mbps
■ Status LED	Link + Data communication
Supply voltage, current consumption, power dissipation, alarm contact	
Connections	
■ Power supply	2 x 0,2 – 2,5 mm ²
■ Functional earthing	1 x 0,2 – 2,5 mm ²
Operating parameters	
■ Supply voltage (nominal value)	24 VDC
■ Supply voltage (min.)	12 VDC
■ Supply voltage (max.)	48 VDC
Environmental conditions	
■ Operating temperature	-40°C ... +75°C
■ Storage temperature	-40°C ... +85°C
■ Humidity, rel.	<95% RHD, non-condensing
Design, Dimensions, Weights	
■ Design	compact, passive cooling
■ Material (housing)	Sheet metal bending housing, lacquered
■ Mounting	35 mm DIN rail (0°, 90°)
■ Width	41 mm
■ Height	103 mm
■ Depth	78 mm
■ Mounting distance (Vertical)	50 mm
■ Mounting distance (horizontal)	20 mm
Further device interfaces	
■ Status LED	PWR
■ Reset	Button
Functions	
Basic parameters	
■ Switching Technology	Store & Forward
■ MAC address table	2 K
■ Packet memory	1 Mbit
■ Backplane capacity	1,6 Gbps
■ Throughput	1,19 Mpps

Unmanaged Switch PROmesh U8

Technical details

Application-specific	
Protocols/Services	
<ul style="list-style-type: none"> PROFINET Conformity Class 	A
Standards, guidelines, approvals	
EMC	
<ul style="list-style-type: none"> Directive 	2014/30/EU
<ul style="list-style-type: none"> interference emission 	EN 55032
<ul style="list-style-type: none"> noise immunity 	EN 61000-6-2
Mechanical stability	
<ul style="list-style-type: none"> Vibration 	IEC 60068-2-6
<ul style="list-style-type: none"> Shock 	IEC 60068-2-27
<ul style="list-style-type: none"> Free Fall 	IEC 60068-2-32
Approval	
<ul style="list-style-type: none"> Europe 	CE/UKCA
Environment	
<ul style="list-style-type: none"> RoHS 	2011/65/EU
<ul style="list-style-type: none"> REACH 	1907/2006/EG

Unmanaged Switch PROmesh U8

Technical Drawing

